## Appendix M Groundwater Monitoring Results for the Juniper Mine

```
(Card 1)
GWSCREEN Version 2.5 - Test Problems
TIME OF RUN: 09:06:30.02 DATE OF RUN: 06/12/01
 *******************
    This output was produced by the model:
            GWSCREEN
           Version 2.5a
    A semi-analytical model for the assessment *
    of the groundwater pathway from the leaching *
    of surficial and buried contamination and
   release of contaminants from percolation ponds *
           04/05/2001
           Arthur S. Rood
      Idaho National Engineering and
        Environmental Laboratory
           PO Box 1625
        Idaho Falls, Idaho 83415
 *****************
```

## ACKNOWLEDGEMENT OF GOVERNMENT SPONSORSHIP AND LIMITATION OF LIABILITY

This material resulted from work developed under U.S. Department of Energy, Office of Environmental Restoration and Waste Management, DOE Field Office, Idaho, Contract Number DE-AC07-76ID01570. This material is subject to a limited government license: Copyright 1993, EG&G Idaho Inc., Idaho National Engineering Laboratory, all rights reserved. Neither the United States nor the United States Department of Energy, nor any of their employees, makes any warranty expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe on privately owned rights. Subroutines GOLDEN, QSIMP, QGAUS, and TRAPZD are Copyright (C) 1992, Numerical Recipes Software. Reproduced by permission from the book, Numerical Recipes, Cambridge University Press.

\_\_\_\_\_\_

```
OUTPUT FILE NAME:
iuniper.out
INPUT FILE NAME:
iuniper.PAR
Title: Nitrate at Juniper mine GWSCREEN Ver 2.5 25 m vert avg source (Card 1)
Model Run Options
IMODE Contaminant Type and Impacts:
                                                      5
ITYPE (1) Vert Avg (2) 3D Point (3) 3d Avg:
                                                      1
IDISP (0) Fixed Dispersivity (1-3) Spatially Varying:
KFLAG (1) Max Conc (2) Conc vs Time (3) Grid Output:
IDIL (1) No dilution factor (2) Include Dilution Factor:
IMOIST Source Moisture Content Option:
                                                      1
IMOISTU Unsaturated Moisture Content Option:
                                                         1
IMODEL (1) Surface/Burried Src (2) Pond (3) Usr Def:
```

ISOLVE (1) Gaussian Quarature (2) Simpsons Rule: (Aquifer)

ISOLVEU (1) Gaussian Quarature (2) Simpsons Rule: (Unsat Zone) 1

Health Effects: Carcinogenic incidence risk for non-radiological contaminants

Output mass/activity units: mg Output concentration units: mg/m\*\*3 Dose/Risk Conversion Units: kg-d/mg

Output health effects units: carcinogenic risk

**Exposure Parameters** 

Body Mass (kg):70.Averaging Time (days):25550.Water Ingestion (L/d):2.000E+00 Exposure Freq (day/ycar):3.500E+02Exposure Duration (y):3.000E+01 Limiting Dose:1.000E-06

Site Parameters

X Coordinate: 0.000E+00 Y Coordinate: 0.000E+00

Source Length (m): 3.050E+00 Source Width (m): 3.050E+00

Percolation Rate (m/y): 1.000E-01

Source Thickness (m): 1.230E+00 Src Bulk Density (g/cc): 1.500E+00

Source Moisture Content: 3.000E-01

**Unsaturated Zone Parameters** 

Unsat Zone Thickness (m): 9.600E+00 Unsat Bulk Density: 1.900E+00 Unsat Dispersivity (m): 1.000E+00 Unsat Moisture Content: 3.000E-01

Aquifer Zone Parameters

4.000E+00 Longitudinal Disp (m): 9.000E+00 Transverse Disp (m): Aguifer Thickness (m): 1.500E+01 Well Screen Thickness (m): 1.500E+01

Darcy Velocity (m/y): 5.700E+01 Aquifer Porosity: 1.000E-01

Bulk Density (g/cc): 1.900E+00

\_\_\_\_\_\_ Calculated Flow Parameters

Percolation Water Flux (m3/y): 9.3025E-01 Unsat Pore Velocity (m/y): 3.3333E-01 Aquifer Pore Velocity (m/y): 5.7000E+02 Longitudinal Disp  $(m^{**}2/y)$ : 5.1300E+03 Transverse Disp  $(m^{**}2/y)$ : 2.2800E+03

\_\_\_\_\_\_

Contaminant Data

\_\_\_\_

Contaminant Name: Nitrate Half Life (y): 1.000E+25

Other Source Loss Rate (1/y): 0.000E+00 Kd Source (ml/g): 0.000E+00 Solubility Limit (mg/L): 1.183E+06 Molecular Weight (mg/L): 8.000E+01 Initial mass/activity: 3.300E+09 Kd Unsat (ml/g): 0.000E+00 0.000E+00

Kd Unsat (ml/g): Kd Aquifer (ml/g): 0.000E+00 Risk/Dose Conversion Factor: 1.000E+00

Calculated Contaminant Values

Decay Constants (1/y): 6.9315E-26 Leach Rate Constant (1/y): 2.7100E-01

Initial Pore Water Conc (Ci or mg/m\*\*3): 9.6136E+08

Solubility Limited Mass (mg): 4.0608E+09
Unsaturated Retardation Factor: 1.0000E+00
Mean Unsaturated Transit Time (y): 2.8800E+01
Leading Edge Arrival Time (y): 2.3751E+00

Aquifer Retardation Factor: 1.000E+00
Minimum Peak Window Time (y): 1.1875E+00
Maximum Peak Window Time (y): 5.4382E+01

Possilta for Possitor V ... 1 52000E .00 V ... 0 0000E .00

## Results for Receptor X = 1.53000E+00 Y = 0.00000E+00

Peak Concentration (mg/m\*\*3): 6.368E+03

Time of Peak (y): 2.7287E+01

Concentrations Averaged Between: 1.2287E+01 and 4.2287E+01 years

Average Concentration (mg/m\*\*3): 4.823E+03

Maximum Dose: 5.663E-02

Maximum Allowable Inventory (mg): 5.827E+04

Execution Time (Seconds): 0